

CL 135 NEW VERSION

APPLICATION INSTRUCTIONS

STEP BY STEP

Step 1

Feed material into laser printer so that the printer is printing on the printable side (white matte coated side).

Step 2

Design your image and and resize if necessary. Print your graphic onto the transfer paper. Use heavy to labels paper mode setting.

Step 3

Prepress fabric for 5-10 seconds

Step 4

Place on shirt with image face down.

Step 5

Heat apply the transfer onto the fabric. Press at 385F for 25 seconds. Use Maximum pressure

Step 6

Release press, wait 4 - 8 seconds, then gently tug at side of shirt and peel backing paper off while warm. After peeling off the backing paper, gently tug sideways along each side of the image. This will soften the feel of the transfer on the shirt.

APPLICATION

ItemNo.: JPCL135A4

| | Fabrics | Fabric Puzzles, Bags |
|--------------|---|---|
| Paper Mode | Heavy to Label* | Heavy to Label* |
| Image | Mirror | Mirror |
| Press Time: | 25-30 sec. | 15 secs |
| Temperature: | 385F (195C) | 380F (190C) |
| Pressure: | Maximum | Maximum |
| Peel: | Warm - Wait 5-10 Seconds before Peeling | Warm - Wait 5-10 Seconds before peeling |
| Wash Temp.: | Up to 105F (40C) | N/A |

*These settings are recommended, you may need to conduct your own tests
All technical information and recommendations are based on tests we have conducted.
Users should conduct their own tests before proceeding

NOTES

Recommended Fabrics

White or Light Colored
100% cotton
100% polyester
Poly/cotton blends
Polyester knits
Polyester mesh
Poly/foam & cotton caps
Satin

Accessories Required

Computer, Color Laser Printer,
Heat Press.

Printable side

The printable side (white matte coated side) without the red lettering.

Pressure Settings

To ensure that the coating has properly fused with the fabric, we recommend to use maximum pressure. If this paper is applied with inadequate pressure, the transfer will not wash well.

Peeling

Wait 4-8 seconds after pressing before you peel. Gently tug along either side of the image, this will soften the feel of the transfer on the shirt.

MousePads

For mouse pads use medium pressure and press at 380F for 15 seconds and peel hot.

Care Instructions

Wait 24 hours before washing.
Machine wash using mild detergent.
Do not use bleach or other aggressive cleaning agents. Cannot be dry cleaned. Wash Temperature cannot exceed 105F

Storage

Keep away from direct heat, sunlight and humidity.